Serret Sekurlast





Mulcher with reversible hydraulic feeder, ideal for pruning of olive trees, citrus trees and nuts.

Adapted to crush residues from 60 mm of diameter, with the rotor SPLINTER of SERRAT which is adapted for tractors between 60 and 120 HP.

It works in reverse to preserve the tractor for doesn't pass at the top of the branches.

CHARACTERISTICS

- Steel-plate chassis, thickness 8 mm.
- ▶ Rotor with SPLINTER technology of Ø 350 mm.
- Gearbox SERRAT for tractors between 60 and 120 HP.
- ► 3 XPC side belt transmission.
- ► Treated blades.
- ► Feeder with system BRALAKC.
- ► High torque hydraulic motor reversible.

- Supports of bearing rotor in steel.
- High speed and high strength bearings.
- ▶ PTO 540 rpm (110 HP).
- ▶ Triple feed chain.
- ▶ 3 lines of counter knives screwed.
- Ground-control rear fixed wheels.
- Model built under EC Normative.
- Safety indicators visible to personnel.

3 lines of counter knives screwed



Rear wheels



MODEL			Þ Q	KG	N° BELTS TYPE							
	mm	КW-НР				A mm	A in	B mm	B in	C mm	C in	
T-1300	1300	45 - 60 88 - 120	36	865	3 XPC	1740	69"	1415	56"	1080	43"	540
T-1500	1500	52 - 70 88 - 120	44	950	3 XPC	1940	76"	1415	56"	1080	43"	540
T-1600*	1600	52 - 70 88 - 120	46	995	3 XPC	2040	80"	1415	56"	1080	43"	540
T-1800	1800	52 - 70 88 - 120	52	1050	3 XPC	2240	88"	1415	56"	1080	43"	540
T-2000	1700	75 - 100 88 - 120	58	1100	3 XPC	2440	96"	1415	56"	1080	43"	540

OPTIONS

► Freewheel

Pick-up tines








22310 Castejón del Puente (Huesca)-España Tel. (+34) 974 417 830 www.serrat.com - comercial@serrat.com



Rotor with SPLINTER technology



► Reversible



▶ Rear roller