



Mulcher designed for tractors between 60 HP to 120 HP for the maintenance of vegetable mantle and for the elimination of remains of pruning up to 80 mm.

Special configuration for frontal works.

CHARACTERISTICS

- ▶ Steel-plate chassis, thickness 10 mm.
- ▶ Rotor POLSER of Ø 450 mm.
- ▶ Gearbox SERRAT.
- ▶ 3 XPC side belt transmission.
- ▶ Forged agricultural hammers SERRAT.
- ▶ Two lines of steel counter hammers.
- ▶ GIROSTOP system into the bolt of the hammer.
- ▶ Supports of bearing rotor in steel.
- ▶ High speed and high strength bearings.
- ▶ Rear height-adjustable roller Ø 180/210 mm (from T-2000).
- ▶ Double bearing on rear roller.
- ▶ Rear gum over the roller.
- ▶ PTO 1,000 rpm.
- ▶ Hydraulic side shift.
- ▶ Hydraulic front hood.
- ▶ Skid shoes.
- ▶ Model built under EC Normative.
- ▶ Safety indicators visible to personnel.




System antiwire in rotor



Rear gum over the roller



| MODEL  |  |  |  |  | Nº BELTS TYPE |  |  |  |  |
|--------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|        | mm                                                                                  | KW-HP                                                                               |                                                                                     | KG                                                                                  |               | A mm-in                                                                             | B mm-in                                                                             | C mm-in                                                                             |                                                                                     |
| T-1600 | 1600                                                                                | 45 - 60<br>90 - 120                                                                 | 12                                                                                  | 720                                                                                 | 3 XPC         | 1825-72"                                                                            | 1035-41"                                                                            | 995-39"                                                                             | 1000                                                                                |
| T-1800 | 1800                                                                                | 45 - 60<br>90 - 120                                                                 | 16                                                                                  | 785                                                                                 | 3 XPC         | 2025-80"                                                                            | 1035-41"                                                                            | 995-39"                                                                             | 1000                                                                                |
| T-2000 | 2000                                                                                | 45 - 60<br>90 - 120                                                                 | 16                                                                                  | 875                                                                                 | 3 XPC         | 2225-88"                                                                            | 1055-42"                                                                            | 995-39"                                                                             | 1000                                                                                |
| T-2300 | 2300                                                                                | 45 - 60<br>90 - 120                                                                 | 20                                                                                  | 1050                                                                                | 3 XPC         | 2525-99"                                                                            | 1385-55"                                                                            | 1060-42"                                                                            | 1000                                                                                |

OPTIONS

- ▶ Freewheel
- ▶ Rounded side



Carretera nacional 240 km. 149,3  
22310 Castejón del Puente (Huesca)-España  
Tel. (+34) 974 417 830  
www.serrat.com - comercial@serrat.com



The data presented in this catalog are provided for information purposes only and are not binding.